



General Certificate of Education

Mathematics 6360

MM2B Mechanics 2B

Mark Scheme

2008 examination - June series

Mark schemes are prepared by the Principal Examiner and considered, together with the relevant questions, by a panel of subject teachers. This mark scheme includes any amendments made at the standardisation meeting attended by all examiners and is the scheme which was used by them in this examination. The standardisation meeting ensures that the mark scheme covers the candidates' responses to questions and that every examiner understands and applies it in the same correct way. As preparation for the standardisation meeting each examiner analyses a number of candidates' scripts: alternative answers not already covered by the mark scheme are discussed at the meeting and legislated for. If, after this meeting, examiners encounter unusual answers which have not been discussed at the meeting they are required to refer these to the Principal Examiner.

It must be stressed that a mark scheme is a working document, in many cases further developed and expanded on the basis of candidates' reactions to a particular paper. Assumptions about future mark schemes on the basis of one year's document should be avoided; whilst the guiding principles of assessment remain constant, details will change, depending on the content of a particular examination paper.

Further copies of this Mark Scheme are available to download from the AQA Website: www.aqa.org.uk

Copyright © 2008 AQA and its licensors. All rights reserved.

COPYRIGHT

AQA retains the copyright on all its publications. However, registered centres for AQA are permitted to copy material from this booklet for their own internal use, with the following important exception: AQA cannot give permission to centres to photocopy any material that is acknowledged to a third party even for internal use within the centre.

Set and published by the Assessment and Qualifications Alliance.

Key to mark scheme and abbreviations used in marking

| | | | |
|--------------|--|-----|----------------------------|
| M | mark is for method | | |
| m or dM | mark is dependent on one or more M marks and is for method | | |
| A | mark is dependent on M or m marks and is for accuracy | | |
| B | mark is independent of M or m marks and is for method and accuracy | | |
| E | mark is for explanation | | |
| √ or ft or F | follow through from previous incorrect result | MC | mis-copy |
| CAO | correct answer only | MR | mis-read |
| CSO | correct solution only | RA | required accuracy |
| AWFW | anything which falls within | FW | further work |
| AWRT | anything which rounds to | ISW | ignore subsequent work |
| ACF | any correct form | FIW | from incorrect work |
| AG | answer given | BOD | given benefit of doubt |
| SC | special case | WR | work replaced by candidate |
| OE | or equivalent | FB | formulae book |
| A2,1 | 2 or 1 (or 0) accuracy marks | NOS | not on scheme |
| -x EE | deduct x marks for each error | G | graph |
| NMS | no method shown | c | candidate |
| PI | possibly implied | sf | significant figure(s) |
| SCA | substantially correct approach | dp | decimal place(s) |

No Method Shown

Where the question specifically requires a particular method to be used, we must usually see evidence of use of this method for any marks to be awarded. However, there are situations in some units where part marks would be appropriate, particularly when similar techniques are involved. Your Principal Examiner will alert you to these and details will be provided on the mark scheme.


Where the answer can be reasonably obtained without showing working and it is very unlikely that the correct answer can be obtained by using an incorrect method, we must award **full marks**. However, the obvious penalty to candidates showing no working is that incorrect answers, however close, earn **no marks**.

Where a question asks the candidate to state or write down a result, no method need be shown for full marks.

Where the permitted calculator has functions which reasonably allow the solution of the question directly, the correct answer without working earns **full marks**, unless it is given to less than the degree of accuracy accepted in the mark scheme, when it gains **no marks**.

Otherwise we require evidence of a correct method for any marks to be awarded.

MM2B

| Q | Solution | Marks | Total | Comments |
|--------------|--|----------------------|----------|---|
| 1(a) | $a = \frac{dy}{dt} = 12t + 4$ | M1 A1 | 2 | |
| (b) | Using $F = ma$, Force = $3 \times (12t + 4)$ When $t = 4$, force = $3(12 \times 4 + 4)$ Force = 156 N | M1 A1 | 2 | |
| (c) | $r = 2t^3 + 2t^2 - 7t + c$ When $t = 0$, $r = 5$, $\therefore c = 5$ $\therefore r = 2t^3 + 2t^2 - 7t + 5$ | M1 A1 M1 A1 | 4 | SC3 if no '+c' seen |
| Total | | | 8 | |
| 2(a) |  | B1 | 1 | |
| (b) | Taking moments about A $2.1 \times 40g = T_B \times 4$ $T_B = 21g$ | M1 B1 A1 | 3 | B1 for 2.1 |
| (c) | Resolve vertically $T_A + T_B = 40g$ $T_A = 19g$ or 186 N | M1 A1 | 2 | |
| (d) | Gravitational force acts through mid point of the rod | E1 | 1 | |
| Total | | | 7 | |
| 3 | $\bar{X} = \frac{25 \times 1 + 12 \times 4 + 4 \times 5}{1 + 4 + 5}$ $= \frac{93}{10}$ or 9.3 $\bar{Y} = \frac{10 \times 1 + 7 \times 4 + 18 \times 5}{10}$ $= \frac{128}{10}$ or 12.8 \therefore Centre of mass is at (9.3, 12.8) | M1 A1 M1 A1 | 4 | Two terms on top correct (+third) and denominator correct SC3 for interchanged \bar{X} and \bar{Y} |
| Total | | | 4 | |

MM2B (cont)

| Q | Solution | Marks | Total | Comments |
|--------------|--|--|-----------|---|
| 4(a) | Using power = force \times velocity Power = $(40 \times 50) \times 50$ $\therefore = 100,000$ watts | M1 A1 | 2 | |
| (b) | When speed is 25, max force exerted is $\frac{100000}{25}$ = 4000N \therefore Accelerating force is 3000N Using $F = ma$ $3000 = 1500 a$ | B1 M1 | | Need 3 terms eg '4000' $\pm 1000 = ma$ or $2000 \pm 1000 = ma$ M0 for $1000 = ma$ |
| (c) | $a = 2 \text{ ms}^{-2}$ When van is at maximum speed force against gravity is $mg \sin 6$ (parallel to slope) Force against gravity and resistance is $mg \sin 6 + 40 v$ = $1536.6 + 40 v$ Speed is maximum when $1536.6 + 40v = \frac{100000}{v}$ $40v^2 + 1536.6v - 100\,000 = 0$ Speed is 34.4 ms^{-1} | A1 B1 M1 A1 M1 A1 A1 | 3 | For 3 terms; $\frac{100000}{v}$ and 1 other term correct CAO |
| Total | | | 11 | |
| 5(a) | $\mathbf{v} = \frac{d\mathbf{r}}{dt}$ $\mathbf{v} = -2 \sin \frac{1}{4}t \mathbf{i} - 2 \cos \frac{1}{4}t \mathbf{j}$ | M1 A1 | 2 | No \mathbf{i}, \mathbf{j} : no marks |
| (b) | Speed is $\{(-2 \sin \frac{1}{4}t)^2 + (-2 \cos \frac{1}{4}t)^2\}^{\frac{1}{2}}$ $= 2 \left(\sin^2 \frac{1}{4}t + \cos^2 \frac{1}{4}t \right)^{\frac{1}{2}}$ = 2 which is a constant | M1 m1 A1 | 3 | clear use of $\sin^2 \theta + \cos^2 \theta = 1$ Use of 2 values SC1 |
| (c) | Magnitude of \mathbf{r} is $\{(8 \cos \frac{1}{4}t)^2 + (8 \sin \frac{1}{4}t)^2\}^{\frac{1}{2}}$ = 8 which is a constant \therefore Particle is moving in a circle | M1 A1 | 2 | $\mathbf{a} = -k\mathbf{r} \Rightarrow$ circle SC2 |
| (d) | Using $v = a\omega$ Angular speed is 0.25 | M1 A1 | 2 | M1 for their $\frac{b}{c}$ if both found |
| (e) | $\mathbf{a} = -\frac{1}{2} \cos \frac{1}{4}t \mathbf{i} + \frac{1}{2} \sin \frac{1}{4}t \mathbf{j}$ | M1 A1 | 2 | |
| (f) | Magnitude of acceleration is $\frac{1}{2}$ | B1 | 1 | |
| Total | | | 12 | |

MM2B (cont)

| Q | Solution | Marks | Total | Comments |
|--------------|---|----------------------------|----------|---|
| 6(a) | Using $F = ma$ $-0.05mv = m \frac{dv}{dt}$ $\therefore \frac{dv}{dt} = -0.05v$ | B1 | 1 | Need to see m terms |
| (b) | $\int \frac{dv}{v} = - \int 0.05 dt$ $\ln v = -0.05t + c$ $v = Ce^{-0.05t}$ When $t = 0, v = 20$, $\therefore C = 20$ $v = 20e^{-0.05t}$ | B1 M1 M1 A1 | 4 | Need first 2 terms } fully correct solutions |
| (c) | When $v = 10, 10 = 20e^{-0.05t}$ $e^{0.05t} = 2$ $\therefore t = \frac{1}{0.05} \ln 2$ $= 13.9$ | M1 A1 A1 | 3 | Accept $20 \ln 2$ |
| Total | | | 8 | |
| 7(a) | At top, for complete revolutions: $\frac{mv^2}{a} = mg$ where v is speed at top $\therefore v^2 = ag$ Conservation of energy from B to top : $\frac{1}{2}mv^2 + mg2a = \frac{1}{2}mu^2$ $u^2 = 4ag + v^2$ $= 5ag$ $u = \sqrt{5ag}$ | M1 A1 M1 A1 A1 | 5 | 3 terms, 2 KE and PE AG |
| (b) | At C , speed of particle is $\sqrt{3ag}$ Resolving horizontally at C : $T = \frac{mv^2}{a}$ $T = m \frac{3ag}{a}$ $T = 3mg$ | B1 M1 A1 | 3 | Needs 2 correct terms |
| (c) | No air resistance Bead is a particle | B1 | 1 | |
| Total | | | 9 | |

MM2B (cont)

| Q | Solution | Marks | Total | Comments |
|--------|--|--|-----------|---|
| 8(a) | $\text{Work done} = \int_0^e \frac{\lambda x}{l} dx$ $= \left[\frac{\lambda x^2}{2l} \right]_0^e$ $= \frac{\lambda e^2}{2l}$ <p>Or Area under a straight line = average force \times distance = $\frac{\lambda e^2}{2l}$</p> | M1 A1 A1 | 3 | Needs limit of 0 AG |
| (b)(i) | Using $T = \frac{\lambda x}{l}$ $5g = \frac{150 \times x}{0.6}$ Extension is 0.196 m | M1 A1 | 2 | |
| (ii) | $\text{EPE} = \frac{\lambda x^2}{2l}$ $= \frac{150 \times (0.3)^2}{2 \times 0.6}$ $= 11.25 \text{ J}$ | M1 A1 | 2 | |
| (iii) | When x above P , $\text{EPE} = \frac{150 \times (0.3 - x)^2}{2 \times 0.6}$ $\text{PE [relative to } P] = (-)5 \times g \times x$ $\text{KE + EPE [at new point]} = \text{EPE [at } P] - \text{gain in PE}$ $\frac{1}{2}mv^2 + \frac{150 \times (0.3 - x)^2}{2 \times 0.6} = \frac{150 \times (0.3)^2}{2 \times 0.6} - 5gx$ $\frac{1}{2}mv^2 + \frac{150 \times (x^2 - 0.6x)}{2 \times 0.6} = -5gx$ $\frac{1}{2} \cdot 5 \cdot v^2 + 125x^2 - 75x = -49x$ $v^2 = 10.4x - 50x^2$ | M1 A1 M1 M1 A1 m1 A1 | 7 | for $\frac{150 \times (\dots - x)^2}{2 \times 0.6}$ for $5 \times g \times \text{distance}$ 4 terms, all signs correct, 2 terms correct Equation involving terms in v^2 , x^2 and x only |
| (iv) | Particle is at rest when $v = 0$ $10.4x - 50x^2 = 0$ $x = 0$ [not required] Or $x = \frac{10.4}{50} = 0.208 \text{ m above } P$. | M1 A1 | 2 | |
| | Total | | 16 | |
| | TOTAL | | 75 | |