

# Mark Scheme (Results) January 2011

GCE

## GCE Physics (6PH01) Paper 01

Edexcel Limited. Registered in England and Wales No. 4496750 Registered Office: One90 High Holborn, London WC1V 7BH



Edexcel is one of the leading examining and awarding bodies in the UK and throughout the world. We provide a wide range of qualifications including academic, vocational, occupational and specific programmes for employers.

Through a network of UK and overseas offices, Edexcel's centres receive the support they need to help them deliver their education and training programmes to learners.

For further information, please call our GCE line on 0844 576 0025, our GCSE team on 0844 576 0027, or visit our website at www.edexcel.com.

If you have any subject specific questions about the content of this Mark Scheme that require the help of a subject specialist, you may find our Ask The Expert email service helpful.

Ask The Expert can be accessed online at the following link:

http://www.edexcel.com/Aboutus/contact-us/

Alternatively, you can speak directly to a subject specialist at Edexcel on our dedicated Science telephone line: 0844 576 0037

January 2011

Publications Code US026587

All the material in this publication is copyright © Edexcel Ltd 2011

### General Marking Guidance

- All candidates must receive the same treatment. Examiners must mark the first candidate in exactly the same way as they mark the last.
- Mark schemes should be applied positively. Candidates must be rewarded for what they have shown they can do rather than penalised for omissions.
- Examiners should mark according to the mark scheme not according to their perception of where the grade boundaries may lie.
- There is no ceiling on achievement. All marks on the mark scheme should be used appropriately.
- All the marks on the mark scheme are designed to be awarded. Examiners should always award full marks if deserved, i.e. if the answer matches the mark scheme. Examiners should also be prepared to award zero marks if the candidate's response is not worthy of credit according to the mark scheme.
- Where some judgement is required, mark schemes will provide the principles by which marks will be awarded and exemplification may be limited.
- When examiners are in doubt regarding the application of the mark scheme to a candidate's response, the team leader must be consulted.
- Crossed out work should be marked UNLESS the candidate has replaced it with an alternative response.

#### Quality of Written Communication

Questions which involve the writing of continuous prose will expect candidates to:

- write legibly, with accurate use of spelling, grammar and punctuation in order to make the meaning clear
- select and use a form and style of writing appropriate to purpose and to complex subject matter
- organise information clearly and coherently, using specialist vocabulary when appropriate.

Full marks will be awarded if the candidate has demonstrated the above abilities. Questions where QWC is likely to be particularly important are indicated (QWC) in the mark scheme, but this does not preclude others.

#### Mark scheme notes

#### Underlying principle

The mark scheme will clearly indicate the concept that is being rewarded, backed up by examples. It is not a set of model answers.

For example:

#### (iii) Horizontal force of hinge on table top

66.3 (N) or 66 (N) **and** correct indication of direction [no ue] ✓ [Some examples of direction: acting from right (to left) / to the left / West / opposite direction to horizontal. May show direction by arrow. Do not accept a minus sign in front of number as direction.] 1

This has a clear statement of the principle for awarding the mark, supported by some examples illustrating acceptable boundaries.

#### 1. Mark scheme format

- 1.1 You will not see 'wtte' (words to that effect). Alternative correct wording should be credited in every answer unless the ms has specified specific words that must be present. Such words will be indicated by underlining e.g. 'resonance'
- 1.2 Bold lower case will be used for emphasis.
- 1.3 Round brackets () indicate words that are not essential e.g. "(hence) distance is increased".
- 1.4 Square brackets [] indicate advice to examiners or examples e.g. [Do not accept gravity] [ecf].

#### 2. Unit error penalties

- 2.1 A separate mark is not usually given for a unit but a missing or incorrect unit will normally mean that the final calculation mark will not be awarded.
- 2.2 Incorrect use of case e.g. 'Watt' or 'w' will **not** be penalised.
- 2.3 There will be no unit penalty applied in 'show that' questions or in any other question where the units to be used have been given, for example in a spreadsheet.
- 2.4 The same missing or incorrect unit will not be penalised more than once within one question (one clip in epen).
- 2.5 Occasionally, it may be decided not to penalise a missing or incorrect unit e.g. the candidate may be calculating the gradient of a graph, resulting in a unit that is not one that should be known and is complex.
- 2.6 The mark scheme will indicate if no unit error penalty is to be applied by means of [no ue].

#### 3. Significant figures

- 3.1 Use of an inappropriate number of significant figures in the theory papers will normally only be penalised in 'show that' questions where use of too few significant figures has resulted in the candidate not demonstrating the validity of the given answer.
- 3.2 The use of  $g = 10 \text{ m s}^2$  or  $10 \text{ N kg}^1$  instead of 9.81 m s<sup>-2</sup> or 9.81 N kg<sup>-1</sup> will be penalised by one mark (but not more than once per clip). Accept 9.8 m s<sup>-2</sup> or 9.8 N kg<sup>-1</sup>

#### 4. Calculations

- 4.1 Bald (i.e. no working shown) correct answers score full marks unless in a 'show that' question.
- 4.2 If a 'show that' question is worth 2 marks then both marks will be available for a reverse working; if it is worth 3 marks then only 2 will be available.
- 4.3 **use** of the formula means that the candidate demonstrates substitution of physically correct values, although there may be conversion errors e.g. power of 10 error.
- 4.4 **recall** of the correct formula will be awarded when the formula is seen or implied by substitution.
- 4.5 The mark scheme will show a correctly worked answer for illustration only.
- 4.6 Example of mark scheme for a calculation:

#### 'Show that' calculation of weight

Use of  $L \times W \times H$ 

Substitution into density equation with a volume and density

Correct answer [49.4 (N)] to at least 3 sig fig. [No ue] [If 5040 g rounded to 5000 g or 5 kg, do not give 3<sup>rd</sup> mark; if conversion to kg is omitted and then answer fudged, do not give 3<sup>rd</sup> mark] [Bald answer scores 0, reverse calculation 2/3]

Example of answer:

 $80 \text{ cm} \times 50 \text{ cm} \times 1.8 \text{ cm} = 7200 \text{ cm}^3$ 

 $7200 \text{ cm}^3 \times 0.70 \text{ g cm}^{-3} = 5040 \text{ g}$ 

 $5040 \times 10^{-3}$  kg × 9.81 N/ kg

= 49.4 N

#### 5. Quality of Written Communication

- 5.1 Indicated by QoWC in mark scheme. QWC Work must be clear and organised in a logical manner using technical wording where appropriate.
- 5.2 Usually it is part of a max mark, the final mark not being awarded unless the QoWC condition has been satisfied.

#### 6. Graphs

- 6.1 A mark given for axes requires both axes to be labelled with quantities and units, and drawn the correct way round.
- 6.2 Sometimes a separate mark will be given for units or for each axis if the units are complex. This will be indicated on the mark scheme.
- 6.3 A mark given for choosing a scale requires that the chosen scale allows all points to be plotted, spreads plotted points over more than half of each axis and is not an awkward scale e.g. multiples of 3, 7 etc.
- 6.4 Points should be plotted to within 1 mm.
  - Check the two points furthest from the best line. If both OK award mark.
  - If either is 2 mm out do not award mark.
  - If both are 1 mm out do not award mark.
  - If either is 1 mm out then check another two and award mark if both of these OK, otherwise no mark.
- 6.5 For a line mark there must be a thin continuous line which is the best-fit line for the candidate's results.

Question Number	Answer	Mark
1	D	1
2	С	1
3	Α	1
4	В	1
5	D	1
6	D	1
7	D	1
8	С	1
9	В	1
10	В	1

Question	Answer	Mark
Number 11*	(QWC – Work must be clear and organised in a logical manner using technical wording where appropriate)(N1:) No acceleration / constant velocity ('constant speed' not sufficient)/ (at rest or) uniform motion in straight line(1)unless unbalanced/ net/ resultant force(1)[Converse: If $\Sigma F = 0$ / forces in equilibrium ('body in equilibrium', 	
	('External force' not sufficient) (For answers based on momentum, 'rate of change of momentum' proportional to force / $F = \Delta(mv)/\Delta t$ )	
	If (resultant) force zero, N2 $\rightarrow$ acceleration = 0 OR acceleration only non-zero if (resultant) force non-zero. (1)	
	Names reversed, max 1 per each correctly, fully defined law (i.e. max 3) Last mark not awarded if laws not explicitly identified within question	
	Total for question 11	5

Question	Answer		Mark
Number			
12*	(QWC – Work must be clear and organised in a logical manner usin technical wording where appropriate)	ıg	
	Small extension hard to measure accurately (or converse)	(1)	
	Small extension gives large percentage uncertainty (or converse)	(1)	
	Max 4 from		
	(thin wire has) small area	(1)	
	stress = force/ area	(1)	
	so get a larger stress (for a given force) / don't need such a large		
	need too much force needed if not thin	(1)	
	greater extension - linked to thinner wire	(1)	
	strain = extension/original length / extension oiginal length	(1)	
	greater extension - linked to longer length	(1)	
	(Alternative to equation marks:		
	Young modulus = stress / strain or $E = Fx / A\Delta x$ (accept alternative	0	
	symbols) scores 1 mark, rearranged to make extension the subject marks)		
	Accept converse arguments (Ignore references to breaking or surface, as in surface area)		Max 5
	Total for question 12		5

Question	Answer	Mark
Number		Warty
13(a)		
	(The graph shows) brittle – undergoes no/little plastic deformation/behaviour (before breaking) / breaks/failsjust beyond/soon after limit of proportionality/elastic limit (1)	
	(The graph shows) ductile – undergoes lots of/significant/large plastic deformation (before breaking) / able to undergo permanent deformation under tensile stress (1)	2
13(b)	Porcelain/vase/it is <u>brittle</u> (1) When broken it doesn't (permanently) deform/ change shape/ bend (or synonyms - but 'dent' is not sufficient) (No elastic deformation not sufficient) (1)	2
	Total for question 13	4

Question Number	Answer	Mark
14(a)(i)	State or show $E_p \rightarrow E_k$ (1) $mgh = \frac{1}{2} mv^2$ Or $gh = \frac{1}{2} v^2$ (1) Use of $mgh = \frac{1}{2} mv^2$ Or $gh = \frac{1}{2} v^2$ (1) v = 3.4 (m s <sup>-1</sup> ) [no ue] (1) Calculation using $v^2 = u^2 + 2as$ scores 0 marks Use of $g = 10$ N kg <sup>-1</sup> gives 3.46 m s <sup>-1</sup> , 3.5 m s <sup>-1</sup> , max 3 marks Do not credit bald answer (Candidates may calculate in steps using $m = 40$ kg, mark 2 becomes use of $E_p = mgh$ and mark 3 becomes use of $E_k = \frac{1}{2} mv^2$ ) Example of calculation $E_p = E_k$ $mgh = 1/2 v^2$ 9.81 N kg <sup>-1</sup> x 0.6 m = $1/2 v^2$ v = 3.4 m s <sup>-1</sup>	4
14(a)(ii)	All $E_p \rightarrow E_k$ / no friction/air resistance / no stretch of cable / $u = 0$ / no push at start / no energy transferred to other forms (1) (No energy lost is not sufficient.)	1
14(b)(i)	Label 2 x tension (7) parallel to cable and away from P only(1)Label weight / pull of child / W/ mg vertically downward(1)One correct and one incorrect scores 1 mark. Two correct and one incorrect scores 1 mark. Two incorrect scores 0.Ignore unlabelled arrows.	2
14(b)(ii)	Use of $W = mg$ (1) Use of correct trigonometrical function (T sin 2 = W/2)(accept with missing factor 2, i.e. T sin 2° = W)(do not accept tan) (accept cos 88)(1) Force = 5600 (N) [no ue] (1) Accept calculation of 11 200 N divided by 2 at the end for full marks only if accompanied by an explanation, such as 'there are two cables' Example of calculation W = mg	3
	W = mg $W = 40 \text{ kg x } 9.81 \text{ N kg}^{-1} = 392 \text{ N}$ $T \sin 2^{\circ} = W/2$ $T = 392 \text{ N} / 2 \text{ x sin } 2^{\circ}$ T = 5621  N Total for question 14	10

Question	Answer	Mark
Number		
15(a)(i)	3 correct labelled arrows:	
	Upthrust, U (1)	
	weight, $W, mg$ (1)	
	(viscous) drag, water resistance, viscous force, V, F, D [upwards] (1)	3
	('resistance' not sufficient)	
	Each incorrect force decreases the maximum possible mark by one	
	U and D can share an arrow.	
	Arrows need not touch particle. Ignore unlabelled arrows.	
15(a)(ii)	upthrust + drag = weight or with unambiguous symbols (allow ecf from	
	diagram) (1)	
	forces in equilibrium / balanced forces / no resultant force / no	2
	acceleration / constant velocity (1)	
15(b) (i)	Down and along (1)	1
	(shape of trajectory not important)	
15(b)(ii)	Lines crossing, eddies, sudden changes in direction,	
	change in direction > 90°, lines disappearing and appearing (1)	1
	Turbulent flow can be seen at any position	
15(b)(iii)	Laminar const vel at a point/no eddies/lines don't cross, but turbulent	
	keeps changing direction/ eddies/ lines cross (1)	1
	Some comparison required.	
	Smooth/streamlined/chaotic not sufficient descriptors	
15(b) (iv)	Turbulent flow $\rightarrow$ eddies/ continual changes will disturb particle back	
	into the flow / stop particle from continuing downwards / lifts particle	1
	Answer should imply some upwards force/ motion imposed on the particle	
	Total for question 15	9

Question Number	Answer	Mark
16(a)	Free body force diagram, arrows must begin at the point shown – including: weight vertical, (W, mg, gravitational force – not 'gravity') friction and/ or air resistance parallel to slope upwards, (D, V, F) normal contact force perpendicular to slope upwards. (ncf, N, R) 3 correct forces = 2 marks, 1 or 2 correct forces = 1 mark, Ignore arrows not coming from point Each incorrect force (e.g. pull down slope) decreases the maximum possible number of creditable forces by one Ignore upthrust.	2
16(b)(i)	Use of equations of motion sufficient to lead to answer (1) $a = 0.9 \text{ (m s}^{-2})$ (1) Example of calculation $s = ut + \frac{1}{2} at^{2}$ $11 \text{ m} = \frac{1}{2} a x (4.9 \text{ s})^{2}$ $a = 0.92 \text{ m s}^{-2}$	2
16(b) ii)	$\begin{array}{l} u = 0.92 \text{ In s} \\ \text{Use of } F = ma \\ F = 36 \text{ to } 40 \text{ N} \\ \hline \text{(1)} \\ \hline \text{Example of calculation} \\ F = ma \\ F = 40 \text{ kg x } 0.92 \text{ m s}^{-2} \\ F = 37 \text{ N} \end{array}$	2
16(c)(i)	Use of trigonometrical relationship (200 cos 20°) to resolve force (1) F = 152  N (1) Example of calculation Horizontal component of force = 200 N x cos 20° = 188 N 37 N = 188 N - resistive force resistive force = 151 N	2
16(c)(ii)	resistive force = 151 NUse of work = force x distance(1)Use of work / time(1)Power = 420 W(1)For $P = Fv$ , Find (or use) ave velocity (1), use of $P = Fv$ (1), correctanswer (1)Example of calculationWork = force x distance= 188 N x 11 m = 2070 JPower = work / time= 2070 J / 4.9 s	3
	= 422 W Total for question 16	11

Question	Answer	Mark
Number	Allswei	IVICIIIK
17(a)(i)	Horizontal component of velocity = $7.5 \cos 50 = 4.8 \text{ (m s}^{-1}$ ) (1)	1
17(a)(ii)	Vertical component of velocity = $7.5 \sin 50 = 5.7 \text{ (m s}^{-1}$ ) (1) May use Pythagoras or tan for second component calculated	1
17(a)(iii)	Use of appropriate equation of motion, e.g. $v = u + at$ , leading to time of flight (1) Time of flight OR double distance travelled half way (1) Use of velocity = distance / time (1) Distance = 5.6 m to 6.1 m (1) Correct answer from range formula 4/4, incorrect answer from range formula 0/4 Example of calculation v=u + at $0 = 5.7 \text{ m s}^{-1} + 9.81 \text{ m s}^{-2} \text{ x t}$ t = 0.58  s to max height time of flight = 1.16 s horizontal distance = horizontal component of velocity x time = 4.8 m s <sup>-1</sup> x 1.16 s = 5.6 m (Using 'show that' values gives 6.12 m)	4
17(b)(i)	Use of $E_k = \frac{1}{2} \text{ mv}^2$ (1) kinetic energy = 41 J (1) Example of calculation $E_k = \frac{1}{2} \frac{mv^2}{m^2}$ m = 2.24  kg - 0.79  kg = 1.45  kg $E_k = \frac{1}{2} \times 1.45 \text{ kg} \times (7.5 \text{ m s}^{-1})^2$ = 40.8  J If answer calculated from difference between 2 kinetic energies, allow first mark only.	2
17(b)(ii)	Not all the mass of liquid which left the bottle went that far / 7.5 m s <sup>-1</sup> is	1
17(b)(iii)	the maximum speed(1)Air resistance / friction at neck(1)could have caused the liquid to lose energy / so the true (initial)velocity is more than the calculated value / so the measured range wasless (than it might otherwise have been)(Just 'energy lost' not sufficient -must be linked to some cause)(1)	2
	Total for question 17	11

Question Number	Answer	Mark
18(a)(i)	Straight line shown / constant gradient (1)	
	(So) extension or change in length proportional to force (accept $\Delta x \text{ or } \Delta l$	
	or <i>e</i> proportional to <i>F</i> ) / <i>k</i> constant. (NOT Length $\alpha$ force) (1)	
	[Just stating $F = k\Delta x$ does not get the mark]	2
	(Yes, because extension or change in length proportional to force gets 2)	
18(a)(ii)	Indication of use of (inverse) gradient, e.g. $k = F/\Delta x$ or with values	
	obtainable from graph (accept extension/force for first mark) (1)	
	Substitution of values as force/ extension(1)Stiffness = $0.66$ to $0.80$ (N m <sup>-1</sup> ) [no ue](1)	3
	Range is due to tolerance of + or – half a square on reading graph.	5
	[Allow answers of $0.7 \text{ N m}^{-1}$ or $0.8 \text{ N m}^{-1}$ without extra sig fig if that is the	
	exact value produced from their figures, e.g. from $F = 0.7 N$ , where	
	length = $260 \text{ cm}$ ]	
	Example of calculation	
	$k = F/\Delta x$	
	k = 0.8  N / (2.7  m - 1.6  m)	
	k = 0.8  N / 1.1  m	
	$= 0.73 \text{ N m}^{-1}$	
	(Read graph to half a square)	
18(a)(iii)	Use of $E = \frac{1}{2} F\Delta x = \frac{1}{2} k(\Delta x)^2$ OR Use of an area between a line and an	
	axis (allow line shown and force axis) (1)	
	Identify correct extension OR correct area (1) $ = 0.24 \text{ Iden} S = 16 \text{ Feb} $	
	$E = 0.31 \text{ J to } 0.35 \text{ J from } E = \frac{1}{2} F \Delta x$ $E = 0.27 \text{ J to } 0.40 \text{ J from } 1/(k(\Delta x)^2) \text{ if } k \text{ in renge follows of for } k \text{ J} = (1)$	3
	$E = 0.27 \text{ J to } 0.40 \text{ J from } \frac{1}{2} k(\Delta x)^2 \text{ if } k \text{ in range [allow ecf for } k] $ (1)	Ŭ
	Example of calculation	
	$\frac{E \times an p c \text{ or calculation}}{E = 1/2 F \Delta x}$	
	= 0.5  x  0.7  N   x  (2.55  m - 1.6  m)	
	= 0.33  J	
18(b)(i)	Coils at top support coils below (1)	
	(So) a greater force acts (on top coils) (1)	2
	Coils at the top support the weight of the coils below as well = 2 marks	
18 (b)(ii)	Clearly below centre and above bottom – accept if no label (1)	1
18 (b)(iii)	(QWC – Work must be clear and organised in a logical manner using	
(1)*	technical wording where appropriate)	
	Ball acted on by its weight (alone) / by gravity (alone) (1)	
	Top coils acted on by their weight and/also acted on by elastic/tension force / force due to extension of coils (1)	
	So the acceleration is greater (1)	
	Energy explanation – max 2	3
	for ball, transfer to ke from gpe alone - 1 mark	
	for top coils, transfer to ke from gpe and elastic $pe -1$ mark	
	(allow 'has' energy instead of transfer to ke)	
18(b)(iii)	They are acted on by weight downwards and (elastic) force upwards/	
(2)	the forces on them are/ remain balanced (1)	1
	Total for question 18	15

GCE Physics 6PH01/01 Results Mark Scheme January 2011

Further copies of this publication are available from Edexcel Publications, Adamsway, Mansfield, Notts, NG18 4FN

Telephone 01623 467467 Fax 01623 450481 Email <u>publications@inneydirect.com</u>

Order Code US026587 January 2011

For more information on Edexcel qualifications, please visit www.edexcel.com/ quals

Edexcel Limited. Registered in England and Wales no.4496750 Registered Office: One90 High Holborn, London, WC1V 7BH